



**HAZLETON CREEK PROPERTIES, LLC**

Wednesday, April 15, 2015

Mr. Jeff Fournier  
Carlin Contracting Co., Inc.  
454 Boston Post Road  
Waterford, CT 06096

Subject: **MDC Project No. 2012-21  
Wet Weather Expansion  
Hartford, CT**

This letter is intended to indicate our intent to accept Non-TSCA PCB-Contaminated Soil with PCB concentrations less than 50 ppm produced by the designated project, subject to and dependent on our subsequent evaluation of waste characterization. Quantity of soil that will be accepted will be determined by our facility daily needs at the time of waste production.

Hazleton Creek Properties, LLC  
282 South Church Street  
Hazleton, PA 18201  
Permit # WMGR096NE001

Representative samples shall be collected and analyzed for each 1000 cubic yards of soil to be considered for disposal acceptance in accordance with the attached PADEP Sample Guidance document. Acceptance criteria are published in the attached General Permit

Should you have any questions, please do not hesitate to call, 570-207-2000 ext 107.  
Thank you for your business.

Very truly yours,

HAZLETON CREEK PROPERTIES, LLC

S:400

Steve Hoats, Operations and Admin.,

## TECHNICAL GUIDANCE:

### FILL DETERMINATION

- 1) To determine whether fill is clean or regulated, a person must perform environmental due diligence.<sup>1</sup>
  - a) If due diligence shows no evidence of a release of a regulated substance, the material may be managed as clean fill under this policy.
  - b) If due diligence shows evidence of a release, the material must be tested to determine if it qualifies as clean fill. Testing must be performed in accordance with Appendix A.
    - i) If testing reveals that the material contains concentrations of regulated substances that are below the residential limits in Table FP-1a and b, the material must be managed as clean fill.
    - ii) If testing reveals that the material contains concentrations of regulated substances that exceed the limits in Table FP-1a and b, the material must be managed as regulated fill.
- 2) A person may not blend or mix materials to become clean fill. Materials that contain regulated substances that are intentionally released may not be managed under this policy.

### MANAGEMENT OF REGULATED FILL

- 1) Materials identified as regulated fill are waste and must be managed in accordance with the Department's municipal or residual waste regulations, whichever is applicable, based on 25 Pa. Code §§ 287.2 or 271.2. Regulated fill may be beneficially used under General Permit WMGR096 (proposed) if the materials and the proposed activities for the fill meet the conditions of that permit. A person may apply for an industry-wide beneficial use general permit for the beneficial use of regulated fill in lieu of this general permit.
- 2) Regulated fill may not be placed on a greenfield property not planned for development, or on a property currently in residential use or planned for residential use unless otherwise authorized.
- 3) Fill containing concentrations of regulated substances that exceed the values in Table GP-1 a and b may not be managed under the provisions of this policy or General Permit WMGR096, but must be otherwise managed in accordance with the provisions of the Department's municipal or residual waste regulations.
- 4) A general permit is not required for remediation activities undertaken entirely on an Act 2 site pursuant to the requirements of Section 902 of the Land Recycling and Environmental Remediation Standards Act. A general permit is also not required if regulated fill from an Act 2 site is used as construction material at a receiving site that is being remediated to attain an Act 2 standard as long as the procedural and substantive requirements of Act 2 are met. Regulated

---

<sup>1</sup> Analytical assessment, testing or sampling is only required if visual inspection or reviews of historic property use indicates evidence of a release of a regulated substance.

substances contained in the regulated fill must be incorporated into the notice of intent to remediate and the final report. Movement of regulated fill between Act 2 sites must be documented in both the sending and receiving sites' cleanup plans and final reports. Placement of the regulated fill may not cause the receiving site undergoing remediation to exceed the selected Act 2 standard.

#### MANAGEMENT OF CLEAN FILL

- 1) Use of material as clean fill does not require a permit under the Solid Waste Management Act and regulations, and it may be used in an unrestricted or unregulated manner under this Act and its regulations. The use of materials as clean fill is still regulated under other environmental laws and regulations. A person using materials as clean fill under the policy is still subject to and must comply with all applicable requirements governing the placement or use of material as clean fill, such as Chapter 102 (Erosion and Sediment Control) and Chapter 105 (Dam Safety and Waterway Management).
- 2) Any person placing clean fill which has been affected by a release of a regulated substance on a property must certify the origin of the fill material and results of analytical testing to qualify the material as clean fill on Form FP-001. Form FP-001 must be retained by the owner of the property receiving the fill.
- 3) Best management practices (BMP) must be followed prior to demolition activities to remove materials like lead-based paint surface, friable asbestos and hazardous materials such as mercury switches, PCB ballasts and fluorescent light bulbs from a building if the brick, block, or concrete is used as clean fill.
- 4) Clean fill may not contain any free liquids based on visual inspection, and shall not create public nuisances (for example objectionable odors) to users of the receiving property or adjacent properties.

## Appendix A

### Sampling and Analyses for Regulated Material to be Used as Fill:

Sampling of regulated material proposed to be used as fill shall be done either by composite samples or by discrete samples. Sampling in either case shall be random and representative of the fill material being sampled. Sampling shall be in accordance with the most current version of the EPA RCRA Manual, SW-846 (*Test Methods for Evaluating Solid Waste, Physical/Chemical Methods. Office of Solid Waste and Emergency Response*).

- (a) Sampling based on composite sampling procedures shall include the following:
  - (i) For volumes of material equal to or less than 125 cubic yards, a total of eight samples shall be collected and analyzed as follows:
    - (A) For analysis of all substances other than volatile organic compounds (VOCs), the samples shall be analyzed in two composites of four samples each, in accordance with the most current version of the USEPA Manual, SW-846 (*Test Methods for Evaluating Solid Waste, Physical/Chemical Methods. Office of Solid Waste and Emergency Response*).
    - (B) Two samples shall be selected from the 8 samples for analysis of VOCs. The samples shall be based on field screening of the eight samples to select those samples that are most likely to contain the highest concentrations of VOCs.
    - (C) Two grab samples shall be taken from the same areas in the material from which the two samples used for field screening of VOCs were taken, in accordance with Method 5035 from the most current version of the USEPA Manual, SW-846 (*Test Methods for Evaluating Solid Waste, Physical/Chemical Methods. Office of Solid Waste and Emergency Response*).
  - (ii) For volumes of material greater than 125 cubic yards and less than or equal to 3,000 cubic yards, a total of 12 samples shall be collected and analyzed as follows:
    - (A) For analysis of all substances other than VOCs, the samples shall be analyzed in three composites of four samples each.
    - (B) Three samples shall be selected from the 12 samples for analysis of VOCs. The samples shall be based on field screening of the 12 samples to select those samples that are most likely to contain the highest concentrations of VOCs.
    - (C) Three grab samples shall be taken from the same areas in the material from which the three samples used for field screening of VOCs were taken, in accordance with EPA Method 5035, referenced in subparagraph (i)(C).

- (iii) For each additional 3,000 cubic yards of material or part thereof over the initial 3,000 cubic yards, 12 additional samples shall be collected and analyzed as follows:
  - (A) For analysis of all substances other than VOCs, the samples shall be analyzed in three composites of four samples each.
  - (B) Three samples for analysis of VOCs shall be selected from the 12 samples for analysis of VOCs. The samples shall be based on field screening of the 12 samples to select those samples that are most likely to contain the highest concentrations of VOCs.
  - (C) Three grab samples shall be taken from the same areas in material from which the three samples used for field screening of VOCs were taken, in accordance with EPA Method 5035, referenced in subparagraph (i)(C).
- (b) Sampling based on discrete sampling procedures shall include the following:
  - (i) For volumes of material equal to or less than 125 cubic yards, a minimum of eight samples shall be collected and analyzed. For volumes of material greater than 125 cubic yards and less than or equal to 3,000 cubic yards, a minimum of 12 samples shall be collected and analyzed. For each additional 3,000 cubic yards of material or part thereof over the initial 3,000 cubic yards, a minimum of 12 additional samples shall be collected and analyzed.
  - (ii) For VOCs analysis, grab sampling procedures shall be the procedures described in subsection (a), for the equivalent volumes of material sampled.
- (c) Analyses of results:
  - (i) For a composite sample taken in accordance with subsection (a), the measured numeric value for a parameter shall be less than or equal to the concentration limit listed in Table FP-1a or b for that parameter in order for the material to qualify as clean fill, or in Table GP-1a or b for that parameter in order for the fill material to qualify as regulated fill.
  - (ii) For a grab sample, taken in accordance with subsections (a) and (b), the measured numeric value for a parameter shall be less than or equal to the concentration limit listed in Table FP-1a or b for that parameter in order for the material to qualify as clean fill, or in Table GP-1a or b for that parameter for the fill material to qualify as regulated fill.
  - (iii) For discrete samples required in subsection (b), the measured numeric values for a substance in 75% of the discrete samples shall be equal to or less than the concentration limit listed in Table FP-1a or b, or in Table GP-1a or b for that parameter with no single sample exceeding more than twice the concentration limit for a parameter.
- (d) In lieu of subsection (c), a person may use 95% Upper Confidence Limit (UCL) of the arithmetic mean to determine whether a fill material meets the appropriate concentration limits for use as clean or regulated fill. The calculated 95% UCL of the arithmetic mean must be below the appropriate concentration limit for clean or regulated fill. Sampling shall be random and

representative of the material being sampled. The minimum number of samples shall be determined in accordance with EPA approved methods on statistical analysis of environmental data, as identified in 25 PA. Code, §250.707(e) (relating to statistical tests). The application of the 95% UCL of the arithmetic mean shall comply with the following performance standards:

- (i) The null hypotheses (Ho) shall be that the true fill arithmetic average concentration is at or above the regulated fill appropriate concentration limit, and the alternative hypothesis (Ha) shall be that the true fill arithmetic average concentration is below the regulated fill appropriate concentration limit.
- (ii) The underlying assumptions of the statistical method shall be met, such as data distribution.
- (iii) Compositing cannot be used for volatile organic compounds.
- (iv) The censoring level for each nondetect shall be the assigned value randomly generated that is between zero and the limit related to the PQL.
- (v) Tests shall account for spatial variability, unless otherwise approved by the Department.
- (vi) Statistical testing shall be done individually for each parameter present in the fill.
- (vii) Where a fill has distinct physical, chemical or biological characteristics, or originates from different areas, the statistical testing shall be done separately.
- (viii) The following information shall be documented:
  - (A) A description of the original areas of the fill, and physical, chemical and biological characteristics of the fill.
  - (B) A description of the underlying assumptions of the statistical method.
  - (C) Documentation showing that the sample data set meets the underlying assumptions of the statistical method.
  - (D) Documentation of input and output data for the statistical test, presented in tables or figures, or both, as appropriate.
  - (E) An interpretation and conclusion of the statistical test.

- (c) The Synthetic Precipitation Leaching Procedure (SPLP, per *Technical Guidance Manual*, 253-0300-100/ May 4, 2002 /Page II-26-27), is listed below:

The value for the SPLP is the concentration of a regulated substance in soil at the site that does not produce a leachate in which the concentration of the regulated substance exceeds the groundwater MSC. Since this test must be conducted on the actual site soil, no values for the SPLP could be published in the tables of MSCs in the regulations. The following procedure should be used to determine the alternative soil-to-groundwater value based upon the SPLP:

- (i) During characterization, the remediator should obtain a minimum of ten samples from within the impacted soil area. The four samples with the highest total concentration of the regulated substance should be submitted for SPLP analysis. Samples obtained will be representative of the soil type and horizon impacted by the release of the regulated substance.
- (ii) Determine the lowest total concentration (TC) that generates a failing SPLP result. The alternative soil-to-groundwater standard will be the next lowest TC.
- (iii) If all samples result in a passing SPLP level, the alternative soil-to-groundwater standard will be the TC corresponding to the highest SPLP result. The remediator has the option of obtaining additional samples.
- (iv) If none of the samples generates a passing SPLP, the remediator can obtain additional samples and perform concurrent TC/SPLP analyses to satisfy the above requirements for establishing an alternative soil-to-groundwater standard.

COMMONWEALTH OF PENNSYLVANIA  
DEPARTMENT OF ENVIRONMENTAL PROTECTION  
BUREAU OF WASTE MANAGEMENT**General Permit  
For  
Processing/Beneficial Use of Municipal Waste**Permit No. WMGR096NE001Date Amended December 23, 2013Date Issued December 23, 2013Date Expires December 23, 2018

The Department of Environmental Protection, Bureau of Waste Management, Division of Municipal and Residual Waste hereby approves the:

☒ Beneficial Use      ☐ Processing prior to Beneficial Use      ☐ Other

of: Regulated fill as defined in Guidance Document 258-2182-773 (Management of Fill).

for use as: Construction material.

This approval is granted to: Hazleton Creek Properties, LLC

Office: 4000 4<sup>th</sup> Avenue.      Site: Bounded by Rts. 924/309 & Broad St.

Moosic, PA 18507      Hazleton, PA 18201

subject to the attached conditions and may be revoked or suspended for any project which the Department of Environmental Protection determines to have a substantial risk to public health, the environment, or cannot be adequately regulated under the provisions of this permit.

The processing of wastes not specifically identified in the documentation submitted for this approval, or the beneficial use of wastes not approved in this permit, is prohibited without the written permission of the Department.

This permit is issued under the authority of the Solid Waste Management Act (35 P.S. §§6018.101-6018.1003), The Pennsylvania Used Oil Recycling Act (58 P.S. §§471-480), The Clean Streams Law (35 P.S. §§691.1-691.1001), Sections 1905-A, 1917-A and 1920-A of the Administrative Code of 1929 (71 P.S. §§510-5, 510-17 and 510-20) and the Municipal Waste Planning, Recycling and Waste Reduction Act (53 P.S. §§4000.101-4000.1904).

This approval is granted:

By: William Foman

☐ Statewide      ☒ Regional

Title: Environmental Program Manager

THIS PERMIT IS NON-TRANSFERABLE

Page 1 of 7



COMMONWEALTH OF PENNSYLVANIA  
DEPARTMENT OF ENVIRONMENTAL PROTECTION  
BUREAU OF WASTE MANAGEMENT**General Permit  
For  
Processing/Beneficial Use of Residual Waste**Permit No. WMGR096Date Amended December 23, 2013Date Issued December 23, 2013Date Expires December 23, 2018

The Department of Environmental Protection, Bureau of Waste Management, Division of Municipal and Residual Waste hereby approves the:

☒ Beneficial Use      ☐ Processing prior to Beneficial Use      ☐ Other

of: regulated fill as defined in Guidance Document 258-2182-773 (Management of Fill)

for use as: construction material.

This approval is granted to: Eligible persons or municipalities qualifying for the general permit.

subject to the attached conditions and may be revoked or suspended for any project which the Department of Environmental Protection determines to have a substantial risk to public health, the environment, or cannot be adequately regulated under the provisions of this permit.

The processing of wastes not specifically identified in the documentation submitted for this approval, or the beneficial use of wastes not approved in this permit, is prohibited without the written permission of the Department.

This permit is issued under the authority of the Solid Waste Management Act (35 P.S. §§6018.101-6018.1003), The Pennsylvania Used Oil Recycling Act (58 P.S. §§471-480), The Clean Streams Law (35 P.S. §§691.1-691.1001), Sections 1905-A, 1917-A and 1920-A of the Administrative Code of 1929 (71 P.S. §§510-5, 510-17 and 510-20) and the Municipal Waste Planning, Recycling and Waste Reduction Act (53 P.S. §§4000.101-4000.1904).

This approval is granted:

By:   
Title: Environmental Program Manager

☒ Statewide      ☐ Regional

THIS PERMIT IS NON-TRANSFERABLE

Page 1 of 7

GENERAL PERMIT NUMBER WMGR096

Regulated Fill

Rev. 12/2013

1. *Permitted Activities.* The approval herein granted is limited to the beneficial use of regulated fill as a construction material when moved offsite or received onsite. Regulated fill may only be moved to a property that is approved for construction and that is zoned and used exclusively for commercial and industrial uses or that is unzoned but is exclusively used for commercial and industrial uses (excluding parks, playgrounds, nursing homes, child care facilities, schools or other residential-style facilities or recreation areas). This permit does not authorize blending or processing of material to meet concentration limits in Table GP-1.
2. *Definitions.* The following terms, when used in this permit, have the following meanings:

*"Regulated fill"* is soil, rock, stone, dredged material, used asphalt, historic fill, and brick, block or concrete from construction and demolition activities that is separate from other waste and recognizable as such that has been affected by a spill or release of a regulated substance and the concentrations of regulated substances exceed the values in Table FP-1 of the Department's fill policy.

*"Historic fill"* is material (excluding landfills, waste piles and impoundments) used to bring an area to grade prior to 1988 that is a conglomeration of soil and residuals, such as ashes from the residential burning of wood and coal, incinerator ash, coal ash, slag, dredged material and construction and demolition waste. The term does not include iron or steel slag that is separate from residuals if it meets the coproduct definition and the requirements of 25 Pa. Code § 287.8. The term does not include coal ash that is separate from residuals if it is beneficially used in accordance with 25 Pa. Code Chapter 290.
3. *Concentration limits.* Regulated fill may not exceed the values in Table GP-1.
4. *Hazardous waste prohibited.* Material that is hazardous waste under Chapter 261a (relating to identification and listing of hazardous waste) may not be used under this permit.
5. *Proper management of fill.* Regulated fill may not be placed on a greenfield property not planned for development, or on a property currently used for or planned for residential use. Material containing concentrations of regulated substances that exceed the values in Table GP-1 may not be moved under the provisions of this general permit, but must be managed in accordance with the provisions of the Department's municipal or residual waste regulations.
6. *Proper management of dredged materials.* In addition to meeting the values in Table GP-1, regulated fill consisting of dredged material from tidal streams shall meet 250 mg/l for chlorides based on an SPLP analysis.
7. *Proper management of fill materials containing metals.* Regulated fill containing metals may be moved to a site if those metals concentrations meet either the concentration limits for metals in Table GP-1 or the background concentration, whichever is higher. Fill that exceeds the concentration limits must be placed as part of an approved construction project in such a manner that all direct contact exposure pathways are eliminated. The background concentration is defined as the concentration of a substance that is present at the site before beneficial use activities occur under this permit. Background concentrations may be determined by taking a representative number of samples, based

GENERAL PERMIT NUMBER WMGR096

Regulated Fill

Rev. 12/2013

on the size of the site, from each of the receiving site and the fill proposed for beneficial use. The average concentration in the receiving site samples becomes the background concentration.

8. *Notice to municipalities.* A person that applies for coverage under this general permit shall submit a copy of the determination of applicability application to each municipality in which the beneficial use activities will be located a minimum of 60 days prior to initiating operations.
9. *Sampling and analysis.* Prior to the beneficial use, the permittee shall perform chemical analysis on representative samples of regulated fill for the appropriate parameters in accordance with the protocol in Appendix A to the Fill Policy. The chemical analyses required in this condition shall be performed by a laboratory accredited or registered for accreditation under the Pennsylvania Environmental Laboratory Accreditation Act of 2002. The operator of the facility shall inspect all incoming waste to insure that the receipt of the waste is consistent with the permit.
10. *Deed Acknowledgment for beneficial use of regulated fill.* The permittee shall provide to the Department proof of a recorded deed notice that includes the exact location of the fill placed on the property, including longitude and latitude descriptions, and a description of the types of fill identified by sampling and analysis. The location and description shall be made a part of the deed for all future conveyances or transfers of the subject property. This deed notice may be provided as an ongoing part of the project or at the end of the completed project.
11. *Siting limitations.* Regulated fill shall not be beneficially used under this permit unless authorized in writing by the Department:
  - a. in the 100-year floodplain;
  - b. within 100 feet of a sinkhole or area draining into a sinkhole;
  - c. within 50 feet of a dwelling unless the owner has provided a written waiver consenting to the beneficial use being closer than 50 feet;
  - d. within 100 feet of a perennial stream;
  - e. within 300 feet of a water source unless the owner has provided a written waiver consenting to the beneficial use being closer than 300 feet;
  - f. within 300 feet of an exceptional value wetland, an exceptional value water or a high quality water.
  - g. The siting limitations in paragraph 11(a) are not applicable to the placement of regulated fill at a brownfield site provided the placement is in accordance with all other applicable requirements.
12. *Water quality.* Regulated fill shall not be placed in the waters of the Commonwealth.

GENERAL PERMIT NUMBER WMGR096

Regulated Fill

Rev. 12/2013

13. *Nuisances.* Regulated fill shall not contain any free liquids based on visual inspection, and shall not create public nuisances (for example objectionable odors) and shall minimize the generation of fugitive dust emissions related to operation of the facility.
14. *Stabilization* Upon completion of areas where regulated fill is beneficially used, the areas shall be promptly vegetated or otherwise stabilized to minimize and control erosion if the construction activity is not undertaken within 30 days of fill placement.
15. *Mixing prohibited.* The regulated fill may not be mixed with other types of solid waste unless otherwise approved by the Department.
16. *Storage and transportation.* The storage and transportation of regulated fill shall be in a manner that does not create a nuisance or be harmful to the public health, safety or the environment. Storage and transportation shall comply with the requirements of 25 Pa. Code Chapters 285 or 299 (relating to storage, collection and transportation of municipal waste and residual waste), whichever is applicable to the waste type being stored or transported.
17. *Discharge of waste prohibited.* This permit does not authorize and shall not be construed as an approval to discharge any other waste, wastewater or runoff from the site where regulated fill originated or the site where regulated fill is beneficially used, to the land or waters of the Commonwealth.
18. *Fugitive emissions.* The permittee shall comply with any applicable fugitive emissions standards adopted under 25 Pa. Code §123.1 and 123.2.
19. *Erosion and sedimentation control.* An erosion and sedimentation control plan shall be implemented that is consistent with the applicable requirements of Chapter 102 (relating to erosion and sedimentation control). A copy of the approved stormwater management, and erosion and sedimentation control plans shall be maintained onsite during construction activities.
20. *Recordkeeping.* Records of analytical evaluations conducted on the regulated fill under this permit, daily records of the weight or volume of the regulated fill received, the placement locations, and the approved construction plans shall be kept onsite by the permittee and at the permittee's place of business. This information shall be available to the Department for inspection and submitted to the Department upon request. This waste analysis information shall be retained by the permittee for a minimum of 5 years.
21. *Relationship to local law.* Nothing in this permit shall be construed to supersede, amend, or authorize a violation of any of the provisions of any valid and applicable local law, ordinance, or regulation, providing that said local law, ordinance, or regulation is not preempted by the Solid Waste Management Act, 35 PS §6018.101 et seq.; and the Municipal Waste Planning, Recycling and Waste Reduction Act of 1988, 53 P.S. §4000.101 et seq.
22. *Inspections.* As a condition of this permit and of the permittee's authority to conduct the activities authorized by this permit, the person receiving the fill hereby authorizes and consents to allow authorized employees or agents of the Department, without advance notice or search warrant, upon presentation of appropriate credentials and without delay, to have access to and to inspect all areas on

GENERAL PERMIT NUMBER WMGR096

Regulated Fill

Rev. 12/2013

which solid waste management activities are being, will be, or have been conducted. This authorization and consent shall include consent to collect samples of waste, soils, water, or gases; to take photographs; to perform measurements, surveys, and other tests; to inspect any monitoring equipment; to inspect the methods of operation; and to inspect and/or copy documents, books, and papers required by the Department to be maintained. This permit condition is referenced in accordance with Sections 608 and 610(7) of The Solid Waste Management Act, 35 P.S. § 6018.608 and 6018.610(7). This condition in no way limits any other powers granted under the Solid Waste Management Act.

23. *Prevention of harm or threat of harm.* The activities authorized by this permit shall not harm or present a threat of harm to the health, safety, or welfare of the people or environment. The Department may modify, suspend, revoke, or reissue the authorization granted in this permit if it deems necessary to prevent harm or the threat of harm to the public health, the environment, or if the activities cannot be adequately regulated under the conditions of this permit.
24. *Individual permits.* The permittee shall comply with the terms and conditions of this general permit and with the environmental protection acts to the same extent as if the activities were covered by an individual permit. The Department may require the permittee to apply for, and obtain an individual permit or cease operation if the permittee is not in compliance with the conditions of this general permit or is conducting an activity that harms or presents a threat of harm to the health, safety or welfare of the people or the environment.
25. *Incorporation of application.* All activities conducted under the authorization granted in this permit shall be conducted in accordance with the permittee's application. Except to the extent that the permit states otherwise, the permittee shall use the regulated fill as described in the approved application.
26. *Permit application requirements.* Persons or municipalities that propose to beneficially use regulated fill by operating under the terms and conditions of this general permit after the date of permit issuance shall submit a determination of applicability application for each location of beneficial use. The application shall be sent to the Department's appropriate regional office that has jurisdiction for waste-related activities in the county where the regulated fill will be beneficially used. At a minimum, the following determination of applicability information shall be submitted on application forms provided by the Department:
  - a. Name and street address of the applicant;
  - b. Names, addresses, and locations of known or potential sources of regulated fill and estimated source weights or volumes;
  - c. Name, location, area and ownership of the location of beneficial use;
  - d. Documentation including laboratory analytical results and a certification by the permittee that the regulated fill meets the conditions of this general permit;
  - e. Number and title of the general permit;

GENERAL PERMIT NUMBER WMGR096

Regulated Fill

Rev. 12/2013

- f. Proof that the beneficial use management activities are consistent with the general permit.
  - g. A description of the activities that will take place and an estimated schedule for placement of regulated fill.
  - h. If the size of the receiving site, where the beneficial use takes place, is greater than or equal to one acre, proof that a Pennsylvania Natural Diversity Inventory (PNDI) review at the site has been completed. This review should be in accordance with the Department's policy #400-0200-001, "Policy for Pennsylvania Natural Diversity Inventory Coordination During Permit Review and Evaluation" (Jan. 18, 2003) and all known occurrences must be resolved with the jurisdictional agency. If a PNDI review has been completed at the receiving site under another Department program, the report of that review and approval may be submitted to the Department to satisfy this permit application requirement.
  - i. Signed and notarized statement by the person who seeks the "determination of applicability" to accept all conditions and operate under the terms and conditions of this general permit;
  - j. Proof that copies of the "determination of applicability" have been submitted to each municipality, county, county planning agency and county health department where the beneficial use is located;
  - k. Proof that the applicant has legal right to enter the land where the beneficial use will occur and perform the activities approved in Condition 1 of this permit and an irrevocable written consent from the landowner giving the Department permission to enter upon land where the applicant will be conducting waste management activities;
  - l. Information that identifies the applicant (i.e. individual, corporation, partnership, government agency, association, etc.) and related parties, including the names and addresses of every officer who has a financial interest in or controls the facility operation;
  - m. Evidence must be provided by persons operating under this general permit of noncompliance with state and federal environmental laws and regulations;
  - n. Independent contractors retained by the applicant to perform any activities authorized under this permit must comply with state and federal laws and regulations relating to environmental protection and transportation safety; and
  - o. The non-refundable fee for a determination of applicability fee, as specified in the residual waste management regulations, payable to the "Commonwealth of Pennsylvania."
- 27 *Commencement of activities.* For persons or municipalities that propose to beneficially use regulated fill on nonresidential brownfields, the activities may commence after 60 working days from the date the determination of applicability application is submitted to the Department, unless otherwise instructed by the Department. A "brownfield" is defined as real property where regulated substances have been released and remain present. For persons or municipalities that propose to beneficially use regulated fill for one of the following, the activities may commence after 60 working days from the

date the determination of applicability application is submitted to the Department, unless otherwise instructed by the Department:

- a. on nonresidential greenfields;
- b. on properties where the area subject to regulated fill placement is larger than 10 acres; or
- c. on properties where waiver or modification of a siting limitation in Condition 11 has been requested.

A "greenfield" is defined as real property that is not a brownfield.

28. *New sources of fill.* If new sources of regulated fill are to be included at the approved beneficial use location, the permittee shall notify the Department in writing by submitting information in accordance with subparts (b) and (d) of Condition 26 above. A permittee may commence with beneficial use of the new source after 10 working days from the date the information is submitted to the Department, unless otherwise instructed by the Department.
29. *Expansions.* If the placement of additional regulated fill will be expanded beyond the permitted area, the permittee shall notify the Department in writing by submitting information in accordance with subparts (a)-(h) and (j) – (k) of Condition 26 above. If additional regulated fill volumes are needed for the approved construction activities within the existing permitted area, the permittee shall submit a letter notifying the appropriate Department regional office. The letter shall include a description of the proposed changes and identify the additional volumes necessary.
30. *Notification of changes in operator.* Any person who is operating under the provisions of this permit shall immediately notify, in writing, the waste program Operations Manager of the appropriate regional office of the Department (address in attached list) within 30 days via certified mail of any changes in: the company name, address, owners, operators, and/or responsible officials of the company; the generator(s) of the regulated fill; the compliance status (e.g., violations) of any permit issued by the Department or federal government under the environmental protection acts
31. *Determination that material is no longer waste.* Regulated fill that meets all the terms and conditions of this permit and that does not exceed concentration limits in Table GP-1 shall cease to be waste once the regulated fill is placed. If dewatered regulated fill is subsequently excavated or moved beyond the area permitted for fill placement, it will then be subject to applicable requirements for the use of regulated fill.
32. *Revocation or suspension.* Failure of the measures herein approved to be performed as intended, or as designed, or in compliance with the applicable laws, rules and regulations, and terms and conditions of this permit, for any reason, shall be grounds for the revocation or suspension of the permittee's approval to operate under this permit.

**Table GP-1a**  
**Regulated Fill Concentration Limits For Organics**

PARAMETER	Regulated Fill	
	Total analysis	
	CASRN	mg/kg
ACENAPHTHENE	83-32-9	4700
ACENAPHTHYLENE	208-96-8	6900
ACEPHATE	30560-19-1	3.6
ACETALDEHYDE	75-07-0	0.63
ACETONE	67-64-1	110
ACETONITRILE	75-05-8	3.9
ACETOPHENONE	98-86-2	540
ACETYLAMINOFLUORENE, 2- (2AAF)	53-96-3	0.28
ACROLEIN	10-702-8	0.0014
ACRYLAMIDE	79-06-1	0.0024
ACRYLIC ACID	79-10-7	0.11
ACRYLONITRILE	107-13-1	0.037
ALACHLOR	15972-80-8	0.077
ALDICARB	116-06-3	0.12
ALDRIN	309-00-2	0.44
ALLYL ALCOHOL	107-18-6	1.2
AMINOSIPHENYL, 4-	92-57-1	0.0046
AMITROLE	61-82-5	0.12
AMMONIA	7664-41-7	360
AMMONIUM SULFAMATE	7773-06-0	24
ANILINE	62-53-3	0.34
ANTHRACENE	120-12-7	350
ATRAZINE	1912-24-9	0.13
BAYGON (PROPOXUR)	114-26-1	0.057
BENOMYL	17804-35-2	970
BENTAZON	25057-89-0	45
BENZENE	71-43-2	0.13
BENZIDINE	92-87-5	0.34
BENZO[A]ANTHRACENE	56-55-3	110
BENZO[A]PYRENE	50-32-8	11
BENZO[B]FLUORANTHENE	205-99-2	110
BENZO[GHI]PERYLENE	191-24-2	180
BENZO[K]FLUORANTHENE	207-08-9	610
BENZOIC ACID	65-85-0	7800
BENZOTRICHLORIDE	98-07-7	0.048
BENZYL ALCOHOL	100-51-6	1100
BENZYL CHLORIDE	100-44-7	0.22
BHC, ALPHA	319-84-6	0.19
BHC, BETA-	319-85-7	0.82
BHC, DELTA-	319-85-8	30
BHC, GAMMA (LINDANE)	58-89-9	0.072
BIPHENYL, 1,1-	92-52-4	2200
BIS(2-CHLOROETHYL)ETHER	111-44-4	0.017
BIS(2-CHLOROISOPROPYL)ETHER	108-60-1	8



**Table GP-1a**  
**Regulated Fill Concentration Limits For Organics**

BIS(CHLOROMETHYL)ETHER	542-86-1	0.00044
PARAMETER		Regulated Fill
		Total analysis
	CASRN	mg/kg
BIS[2-ETHYLHEXYL] PHTHALATE	117-81-7	130
BISPHENOL A	80-05-7	2000
BROMACIL	314-40-9	2
BROMOCHLOROMETHANE	74-97-5	1.6
BROMODICHLOROMETHANE	75-27-4	3.4
BROMOMETHANE	74-83-9	0.54
BROMOXYNIL	1689-84-5	170
BROMOXYNIL OCTANOATE	1689-99-2	350
BUTADIENE, 1,3-	106-99-0	0.027
BUTYL ALCOHOL, N-	71-36-3	24
BUTYLATE	2008-41-5	51
BUTYLBENZENE, N-	104-51-8	2600
BUTYLBENZENE, SEC-	135-98-8	960
BUTYLBENZENE, TERT-	98-06-6	740
BUTYLBENZYL PHTHALATE	85-58-7	10000
CAPTAN	133-06-2	31
CARBARYL	63-25-2	41
CARBAZOLE	86-74-8	83
CARBOFURAN	1563-86-2	0.87
CARBON DISULFIDE	75-15-0	350
CARBON TETRACHLORIDE	56-23-5	0.26
CARBOXIN	5234-88-4	53
CHLORAMBEN	133-90-4	1.6
CHLORDANE	57-74-9	49
CHLORO-1,1-DIFLUOROETHANE, 1-	75-68-3	4800
CHLORO-1-PROPENE, 3- (ALLYL CHLORIDE)	107-05-1	0.13
CHLOROACETOPHENONE, 2-	532-27-4	0.026
CHLOROANILINE, P-	106-47-8	52
CHLOROBENZENE	108-90-7	6.1
CHLOROBENZILATE	510-15-6	6.3
CHLOROBUTANE, 1-	109-59-3	6400
CHLORODIBROMOMETHANE	124-48-1	3.2
CHLORODIFLUOROMETHANE	75-45-6	2.6
CHLOROETHANE	75-00-3	19
CHLOROFORM	67-66-3	2.5
CHLORONAPHTHALENE, 2-	91-58-7	18000
CHLORONITROBENZENE, P-	100-00-5	18
CHLOROPHENOL, 2-	95-57-8	4.4
CHLOROPRENE	126-99-8	0.97
CHLOROPROPANE, 2-	75-29-6	44
CHLOROTHALONIL	1897-45-6	61
CHLOROTOLUENE, O-	95-49-8	20
CHLORPYRIFOS	2921-88-2	23

**Table GP-1a**  
**Regulated Fill Concentration Limits For Organics**

CHLORSULFURON	64902-72-3	71
CHLORTHAL-DIMETHYL (DACTHAL) (DCPA)	1861-32-1	650
PARAMETER		Regulated Fill
		Total analysis
	CASRN	mg/kg
CHRYSENE	218-01-9	230
CRESOL(S)	1319-77-3	8.9
CRESOL, O- (METHYLPHENOL, 2-)	95-48-7	180
CRESOL, M (METHYLPHENOL, 3-)	108-39-4	100
CRESOL, P (METHYLPHENOL, 4-)	106-44-5	12
CRESOL, P-CHLORO-M-	59-50-7	110
CROTONALDEHYDE	4170-30-3	0.0043
CROTONALDEHYDE, TRANS-	123-73-9	0.0043
CUMENE	98-82-8	1600
CYCLOHEXANONE	108-94-1	2800
CYFLUTHRIN	68359-37-5	33
CYROMAZINE	66215-27-8	240
DDO, 4,4'-	72-54-8	30
DDE, 4,4'-	72-55-9	170
DDT, 4,4'-	50-29-3	230
DI(2-ETHYLHEXYL)ADIPATE	103-23-1	10000
DIALATE	2303-16-4	0.59
DIAMINOTOLUENE, 2,4-	95-80-7	0.616
DIAZINON	333-41-5	0.062
DIBENZO[A,H]ANTHRACENE	53-70-3	11
DIBROMO-3-CHLOROPROPANE, 1,2-	96-12-8	0.0092
DIBROMOBENZENE, 1,4-	106-37-6	410
DIBROMOETHANE, 1,2- (ETHYLENE DIBROMIDE)	106-93-4	0.0012
DIBROMOMETHANE	74-95-3	7.7
DIBUTYL PHTHALATE, N-	84-74-2	4100
DICHLORO-2-BUTENE, 1,4-	764-41-0	0.0039
DICHLOROBENZENE, 1,2-	95-50-1	59
DICHLOROBENZENE, 1,3-	541-73-1	61
DICHLOROBENZENE, P-	106-46-7	10
DICHLOROBENZIDINE, 3,3'-	91-94-1	32
DICHLORODIFLUOROMETHANE (FREON 12)	75-71-8	100
DICHLOROETHANE, 1,1-	75-34-3	2.7
DICHLOROETHANE, 1,2-	107-06-2	0.1
DICHLOROETHYLENE, 1,1-	75-35-4	0.19
DICHLOROETHYLENE, CIS-1,2-	156-59-2	1.6
DICHLOROETHYLENE, TRANS-1,2-	156-60-5	2.3
DICHLOROMETHANE (METHYLENE CHLORIDE)	75-09-2	0.076
DICHLOROPHENOL, 2,4-	120-83-2	1
DICHLOROPHOXYACETIC ACID, 2,4- (2,4-D)	94-75-7	1.3
DICHLOROPROPANE, 1,2-	78-87-5	0.11
DICHLOROPROPENE, 1,3-	542-75-6	0.46
DICHLOROPROPIONIC ACID (DALAPON), 2,2-	75-99-0	5.3

**Table GP-1a**  
**Regulated Fill Concentration Limits For Organics**

DICHLORVOS	62-73-7	0.052
DICYCLOPENTADIENE	77-73-6	0.26
PARAMETER		Regulated Fill
		Total analysis
	CASRN	mg/kg
DIELDRIN	60-57-1	0.44
DIETHYL PHTHALATE	84-66-2	160
DIFLUBENZURON	35367-38-5	52
DIMETHOATE	60-51-5	0.77
DIMETHOXYBENZIDINE, 3,3-	119-90-4	64
DIMETHYLAMINOAZOBENZENE, P-	60-11-7	0.15
DIMETHYLANILINE, N,N-	000121-69-7	11
DIMETHYLBENZIDINE, 3,3-	000119-93-7	1.5
DIMETHYLPHENOL, 2,4-	105-67-9	87
DINITROBENZENE, 1,3-	99-65-0	0.049
DINITROPHENOL, 2,4-	51-28-5	0.46
DINITROTOLUENE, 2,4-	121-14-2	0.2
DINITROTOLUENE, 2,6- (2,6-DNT)	605-20-2	3
DINOSEB	58-85-7	0.29
DIOXANE, 1,4-	123-91-1	0.31
DIPHENAMID	957-51-7	12
DIPHENYLAMINE	122-39-4	12
DIPHENYLHYDRAZINE, 1,2-	122-66-7	0.58
DIQUAT	85-00-7	0.24
DISULFOTON	298-04-4	0.078
DIURON	330-54-1	0.86
ENDOSULFAN	115-29-7	61
ENDOSULFAN I (ALPHA)	959-98-8	260
ENDOSULFAN II (BETA)	33213-65-9	260
ENDOSULFAN SULFATE	1031-07-8	70
ENDOTHALL	145-73-3	4.1
ENDRIN	72-20-8	5.5
EPICHLOROHYDRIN	106-89-8	0.12
ETHEPHON	16672-87-0	5.9
ETHION	583-12-2	110
ETHOXYETHANOL, 2- (EGEE)	110-80-5	17
ETHYL ACETATE	141-78-6	470
ETHYL ACRYLATE	140-88-5	0.5
ETHYL BENZENE	100-41-4	46
ETHYL DIPROPYLTHIOCARBAMATE, S- (EPTC)	759-94-4	180
ETHYL ETHER	60-29-7	120
ETHYL METHACRYLATE	97-63-2	30
ETHYLENE GLYCOL	107-21-1	170
ETHYLENE THIOUREA (ETU)	96-45-7	0.034
ETHYLP-NITROPHENYL PHENYLPHOSPHOROTHIOATE	2104-64-5	0.31
FENAMIPHOS	22224-92-6	0.17
FENVALERATE (PYDRIN)	51630-58-1	94

**Table GP-1a**  
**Regulated Fill Concentration Limits For Organics**

FLUOMETURON	2164-17-2	2.5
FLUORANTHENE	206-44-0	3200
PARAMETER		Regulated Fill
		Total analysis
	CASRN	mg/kg
FLUORENE	86-73-7	3800
FLUOROTRICHLOROMETHANE (FREON 11)	75-69-4	87
FONOFOS	944-22-9	2.9
FORMALDEHYDE	50-00-0	12
FORMIC ACID	64-18-6	450
FOSETYL-AL	39148-24-8	27000
FURAN	110-00-9	0.87
FURFURAL	98-01-1	3.7
GLYPHOSATE	1071-83-6	620
HEPTACHLOR	76-44-8	0.68
HEPTACHLOR EPOXIDE	1024-57-3	1.1
HEXACHLOROBENZENE	118-74-1	0.96
HEXACHLOROBUTADIENE	87-68-3	1.2
HEXACHLOROCYCLOPENTADIENE	77-47-4	91
HEXACHLOROETHANE	67-72-1	0.56
HEXANE	110-54-3	1100
HEXYTHIAZOX (SAVEY)	78587-05-0	820
HYDRAZINE/HYDRAZINE SULFATE	302-01-2	0.00042
HYDROQUINONE	123-31-9	55
INDENO[1,2,3-CD]PYRENE	193-39-5	110
IPRODIONE	36734-19-7	1200
ISOBUTYL ALCOHOL	78-83-1	160
ISOPHORONE	78-59-1	1.9
KEPONE	143-50-0	2.2
MALATHION	121-75-5	34
MALEIC HYDRAZIDE	123-33-1	47
MANEB	12427-38-2	5.8
MERPHOS OXIDE	78-48-8	41
METHACRYLONITRILE	126-96-7	0.067
METHAMIDOPHOS	10265-92-6	0.063
METHANOL	67-56-1	120
METHOMYL	16752-77-5	3.2
METHOXYCHLOR	72-43-5	630
METHOXYETHANOL 2-	109-86-4	1.1
METHYL ACETATE	79-20-9	1900
METHYL ACRYLATE	96-33-3	77
METHYL CHLORIDE	74-87-3	0.038
METHYL ETHYL KETONE	78-93-3	110
METHYL ISOBUTYL KETONE	108-10-1	5.3
METHYL METHACRYLATE	80-62-6	56
METHYL METHANESULFONATE	66-27-3	0.32
METHYL PARATHION	298-00-0	0.42

**Table GP-1a**  
**Regulated Fill Concentration Limits For Organics**

METHYL STYRENE (MIXED ISOMERS)	25013-15-4	340
METHYL TERT-BUTYL ETHER (MTBE)	1634-04-4	0.28
PARAMETER		Regulated Fill
		Total analysis
	CASRN	mg/kg
METHYLENE BIS(2-CHLOROANILINE), 4,4'-	101-14-4	15
METHYLNAPHTHALENE, 2-	91-57-6	8000
METHYLSTYRENE, ALPHA	98-83-9	250
NAPHTHALENE	91-20-3	25
NAPHTHYLAMINE, 1-	134-32-7	1.1
NAPHTHYLAMINE, 2-	91-59-8	0.046
NAPROPAMIDE	15299-99-7	2300
NITROANILINE, M-	99-09-2	0.091
NITROANILINE, O-	88-74-4	0.1
NITROANILINE, P-	100-01-6	0.086
NITROBENZENE	98-95-3	2.2
NITROPHENOL, 2-	88-75-5	17
NITROPHENOL, 4-	100-02-7	4.1
NITROPROPANE, 2-	79-46-9	0.0011
NITROSODIETHYLAMINE, N-	55-18-5	0.000076
NITROSODIMETHYLAMINE, N-	62-75-9	0.00017
NITROSO-DI-N-BUTYLAMINE, N-	924-16-3	0.014
NITROSODI-N-PROPYLAMINE, N-	621-64-7	0.0051
NITROSODIPHENYLAMINE, N-	86-30-6	83
NITROSO-N-ETHYLUREA, N-	759-73-9	0.00022
OCTYL PHTHALATE, DI-N-	117-84-0	10000
OXAMYL (VYDATE)	28135-22-0	2.6
PARATHION	56-38-2	360
PCB-1016 (AROCOR)	12674-11-2	200
PCB-1221 (AROCOR)	11104-28-2	2.5
PCB-1232 (AROCOR)	11141-16-5	2
PCB-1242 (AROCOR)	53469-21-9	62
PCB-1248 (AROCOR)	12672-29-6	44
PCB-1254 (AROCOR)	11097-69-1	44
PCB-1260 (AROCOR)	11096-82-5	130
PEBULATE	1114-71-2	860
PENTACHLOROBENZENE	608-93-5	660
PENTACHLORONITROBENZENE	82-68-8	20
PENTACHLOROPHENOL	87-86-5	5
PHENACETIN	62-44-2	48
PHENANTHRENE	85-01-8	10000
PHENOL	108-95-2	66
PHENYLENEDIAMINE, M-	108-45-2	8.6
PHENYLPHENOL, 2-	90-43-7	1900
PHORATE	298-02-2	0.88
PHTHALIC ANHYDRIDE	85-44-9	6200
PICLORAM	1918-02-1	7.4
PRONAMIDE	23950-58-5	3.1

Table GP-1a  
Regulated Fill Concentration Limits For Organics

PROPANIL	709-95-8	25
PROPHAM	122-42-9	48
PARAMETER		Regulated Fill
		Total analysis
	CASRN	mg/kg
PROPYLBENZENE, N-	103-65-1	780
PROPYLENE OXIDE	75-56-9	0.19
PYRENE	129-00-0	2200
PYRIDINE	110-85-1	0.22
QUINOLINE	91-22-5	0.074
QUIZALOFOP (ASSURE)	76578-14-8	47
RONNEL	299-84-3	800
SIMAZINE	122-34-9	0.15
STRYCHNINE	57-24-9	2.5
STYRENE	100-42-5	24
TEBUTHIURON	34014-18-1	83
TERBACIL	5902-51-2	2.2
TERBUFOS	13071-79-9	0.12
TETRACHLOROBENZENE, 1,2,4,5-	95-94-3	14
TETRACHLORODIBENZO-P-DIOXIN, 2,3,7,8- (TCDD)	1746-01-6	0.00053
TETRACHLOROETHANE, 1,1,1,2-	630-20-6	18
TETRACHLOROETHANE, 1,1,2,2-	79-34-5	0.0093
TETRACHLOROETHYLENE (PCE)	127-18-4	0.43
TETRACHLOROPHENOL, 2,3,4,6-	58-90-2	950
TETRAETHYL LEAD	78-00-2	0.012
TETRAETHYLDITHIOPYROPHOSPHATE	3689-24-5	1.5
THIOFANOX	39195-18-4	0.34
THIRAM	137-26-8	130
TOLUENE	108-88-3	44
TOLUIDINE, M-	108-44-1	0.51
TOLUIDINE, O-	95-53-4	1.2
TOLUIDINE, P-	106-49-0	1.3
TOXAPHENE	8001-35-2	1.2
TRIALATE	2303-17-5	660
TRIBROMOMETHANE (BROMOFORM)	75-25-2	4.4
TRICHLORO-1,2,2-TRIFLUOROETHANE, 1,1,2-	76-13-1	53000
TRICHLOROBENZENE, 1,2,4-	120-82-1	27
TRICHLOROBENZENE, 1,3,5-	108-70-3	31
TRICHLOROETHANE, 1,1,1-	71-55-6	7.2
TRICHLOROETHANE, 1,1,2-	79-00-5	0.15
TRICHLOROETHYLENE (TCE)	79-01-6	0.17
TRICHLOROPHENOL, 2,4,5-	95-95-4	6100
TRICHLOROPHENOL, 2,4,6-	88-06-2	8.9
TRICHLOROPHOXYACETIC ACID, 2,4,5- (2,4,5-T)	93-76-5	1.5
TRICHLOROPHOXYPROPIONIC ACID, 2,4,5- (2,4,5-TP) (SILVEX)	93-72-1	22
TRICHLOROPROPANE, 1,1,2-	596-77-6	8.7
TRICHLOROPROPANE, 1,2,3-	96-18-4	0.82

**Table GP-1a**  
**Regulated Fill Concentration Limits For Organics**

TRICHLOROPROPENE, 1,2,3-	96-19-5	30
TRIFLURALIN	1582-09-8	0.96
PARAMETER		Regulated Fill
		Total analysis
	CASRN	mg/kg
TRIMETHYLBENZENE, 1,3,4- (TRIMETHYLBENZENE, 1,2,4-)	95-63-6	20
TRIMETHYLBENZENE, 1,3,5-	108-67-8	6.2
TRINITROTOLUENE, 2,4,6-	118-95-7	0.023
VINYL ACETATE	106-05-4	14
VINYL BROMIDE (BROMOETHENE)	593-60-2	0.28
VINYL CHLORIDE	75-01-4	0.027
WARFARIN	81-81-2	7.4
XYLENES (TOTAL)	1330-20-7	990
ZINES	12122-67-7	81

Table GP-1b

## Regulated Fill Concentration Limits for Metals and Inorganics

PARAMETER	CASRN	Regulated Fill
		Total Analysis
		mg/kg
ALUMINUM	7429-90-5	190000
ANTIMONY	7440-36-0	27
ARSENIC	7440-38-2	53
BARIUM AND COMPOUNDS	7440-39-3	8200
BERYLLIUM	7440-41-7	320
BORON AND COMPOUNDS	7440-42-8	5.7
CADMIUM	7440-43-9	38
CHROMIUM III	16065-83-1	190000
CHROMIUM VI	18540-29-9	190
COBALT	7440-48-4	22
COPPER	7440-50-8	36000
CYANIDE, FREE	57-12-5	200
IRON	7439-89-6	180000
LEAD	7439-92-1	<b>943</b>
MANGANESE	7439-96-5	190000
MERCURY	7439-97-6	10
NICKEL	7440-02-0	650
NITRATE NITROGEN	14797-55-8	na
NITRITE NITROGEN	14797-65-0	na
SELENIUM	7782-49-2	25
SILVER	7440-22-4	84
THALLIUM	7440-28-0	14
TIN	7440-31-5	680
VANADIUM	7440-62-2	72000
ZINC	7440-66-6	12000